










CNT	HYDRAULIC CONTROL UNIT
CNT	HYDRAULIK STEUERGERÄT
CNT	CENTRAL HIDRÁULICA
CNT	CENTRALE HYDRAULIQUE



							
mod.	cod.	HP	lt	l/min	bar	cm	kg tot.
CNT singola	1003171	30 - 100	80	45	max 180	90×97×112	235
CNT doppia	1003089	30 - 100	80	45 + 45	max 180	90×97×112	270

Di serie	Standard equipment	Serienmässig	Estándar	De série
<ul style="list-style-type: none"> • Attacco a 3 punti Cat. II • Centralina idraulica completa di: <ul style="list-style-type: none"> - serbatoio, - sistema filtrante - scambiatore di calore con termostato - valvola di massima • Ruote di appoggio regolabili in altezza • Freno di stazionamento per rimessaggio • innesti rapidi: <ul style="list-style-type: none"> - 1 mandata e 2 scarichi (versione singola), - 2 mandata e 4 scarichi (versione doppia) • Protezioni antinfortunistiche conformi alla normativa CE 	<ul style="list-style-type: none"> • 3-point linkage cat. II • Hydraulic control unit complete with: <ul style="list-style-type: none"> - tank - filter system - heat exchanger with thermostat - relief valve • Height-adjustable wheels • Parking brake for storage • Quick couplings: <ul style="list-style-type: none"> - 1 delivery and 2 drainage (single version), - 2 delivery and 4 drainages (double version) • Protective equipment as per EC safety rules 	<ul style="list-style-type: none"> • 3-Punkt-Anbau Kat. II • Hydraulik Steuergerät komplett mit: <ul style="list-style-type: none"> - Tank - Filtersystem - Wärmetauscher mit Thermostat - Entlastungsventil • Höhenverstellbare Räder • Feststellbremse zur Aufbewahrung • Schnellkupplungen: <ul style="list-style-type: none"> - 1 Druckleitung und 2 Ölableitungen (Einzelversion), - 2 Druckleitungen und 4 Ölableitungen (Doppelversion) • Unfallschutz nach EU-Vorschriften 	<ul style="list-style-type: none"> • Eenganche a 3 punto Cat. II • Central hidráulica completa de: <ul style="list-style-type: none"> - depósito (litros) - sistema filtrante - intercambiador de calor con termostato - válvula de seguridad • Rueda de apoyo con regulación en altura • Freno de estacionamiento para almacenamiento • Enchufes rápidos: <ul style="list-style-type: none"> - 1 impulsión y 2 retorno (versión simple), - 2 impulsión y 4 retorno (versión doble) • Protecciones de seguridad de acuerdo con la norma CE 	<ul style="list-style-type: none"> • Attelage 3 points Cat. II • Unité de commande hydraulique complète avec: <ul style="list-style-type: none"> - réservoir - système de filtrage - échangeur de chaleur avec thermostat - soupape de surpression • Roues de support réglables en hauteur • Frein de stationnement pour le stockage • Raccords rapides: <ul style="list-style-type: none"> - 1 refoulement et 2 échappements (version simple), - 2 refoulements et 4 échappements (version double) • Protections contre les accidents aux normes CE